

# HEAVYWEIGHT STOPPING POWER

New-to-range from  
**Haldex**

## Grau 24/30 brake chamber TECHNICAL SPECIFICATIONS

Version	24/30
Push rod (mm)	285
Push rod thread	M16 x 1.5
Protection	Wiper
Yoke	c/w
Side port	M16 x 1.5
Mounting thread	M16 x 1.5
Breather pipe	w/o
Side port (degrees)	90
Max. operating pressure (bar)	10
Stroke (mm)	76

Part no.  
**3462430101**

### KEY BENEFITS

- Internal coil spring diameter is 0.5 mm larger than spring used in other manufacturer's designs, improving lifetime of spring by > 30%
- Surface treatment and anti-corrosion coating protect against salt spray
- Double "O" ring sealed centre section protects against air leakage and prolongs service life
- Special crimping method eliminates the risk of accidental release of the power spring and enables low profile clamp-free interference
- Steel inner rod and slotted centre seal design improves the alignment of moving parts, prevents premature wear of seals and increases service life
- The travel indicator provides a visual inspection function for proper brake adjustment

Because it's from Haldex, every Grau brake chamber is tested to the most rigorous standards. All testing is carried out in accordance with SAE J1469.

Durable and reliable, Grau products are thoroughly tested for compliance with Haldex standards and come with a full warranty.

