



DIAGRAM OF SERVICE BRAKE TYPE 36

FORCE OF RETURN SPRING AT 0 STROKE : 250 ± 25 N
 AIR VOLUME OF SERVICE BRAKE PART AT 2/3 OF ITS STROKE : < 1.6 cm³

| | |
|-----------------------------|---------------------------|
| MEDIA | HAVA AIR |
| OPERATING TEMPERATURE RANGE | -40°C + 80°C |
| OPERATING PRESSURE | Max. 10 bar |
| MAXIMUM PRESSURE | 13 bar |
| PERMISSIBLE LEAKAGE | 10 cm ³ / min. |
| WEIGHT | |

Haldex-BESTELL-NR.
 Haldex PART NO.

| ALLGEME INTOLERANZEN/GENERAL TOLERANCES | | | | | |
|---|--|------|---------------|----------------|-------|
| CLASS | ABMESSUNGEN VON-BIS/RANGE OF NOMINAL DIMENSIONS (±) MM | | | | |
| | HIER: THIS PART: | ≤ 50 | > 50 ≤ 150 | > 150 ≤ 400 | > 400 |
| A | | 0,5 | 1,0 | 1,5 | 2,0 |
| B | X | 1,0 | 2,0 | 3,0 | 4,0 |
| C | | 2,0 | 3,5 | 5,0 | 6,5 |

| | | | | | | |
|--------------------------|-------------------------|--|---|----------------------|-----------|-----------|
| DC RHOADS 13 AUG 2010 | MASSTAB 1:1 | BEZEICHNUNG/DESIGNATION MEMBRANZYLINDER TYP 36 BRAKE CHAMBER | IND.-ANZ. 1 | STATUS NO. 10-006 | DAY. 1 | NAME 1 |
| GEZ. OGE 13-AUG-10 | NRH. BF 13-Aug-10 | | ZEICHNUNG NR./DWG NO. 123 360 004 | | INDEX | PAUSE |
| | | | PROJECT 10-006 | BLATT ANZ. 1 | | |

CAD - ZEICHNUNG, MANUELLE AENDERUNGEN ZULAESSIG

Haldex
 Brake Products GmbH