


PART No.
364 591 000 2

COMPUTER PRODUCED DRAWING
MUST NOT BE CHANGED MANUALLY



- N 1 SEE CHART 'A' FOR CABLE ASSEMBLY PART NUMBER.
- N 2 CABLE IS SUPPLIED COILED IN A PLASTIC BAG
- N 3 CABLE INSULATION MATERIAL
- PVC
WIRE CROSS SECTIONAL AREA
- 3 x 1.50mm²
- 2 x 4.00mm²
- N 4 CONFORMS TO IP67 (BS EN 60529) WHEN MATED WITH UABS ECU / JUNCTION BOX
- N 5 SEAL TO BE PROTECTED FROM DAMAGE PRIOR TO ASSEMBLY
- N 6 PART NUMBER IDENTIFICATION
- N 7 PROTECTIVE CAP - DO NOT REMOVE UNTIL FITMENT TO ECU / JUNCTION BOX

CHART A	
ASSY. No.	LENGTH
364 591 001	2.5m
364 591 011	4m

K **M**
T THIS DRAWING/SPECIFICATION USES CLASSIFIED CHARACTERISTIC SYMBOLS DEFINED IN QUALITY PROCEDURE 4.17

ISS	CHANGE	CHEC	DATE	ISS	CHANGE	CHEC	DATE
2	C6436	MPH	14-05-13				
1	PR2080_5	MPH	11-06-12				

AutoCAD PART
THIS DRAWING/DOCUMENT IS COPYRIGHT AND THE PROPERTY OF HALDEX BRAKE PRODUCTS LIMITED. IT MUST NOT BE COPIED (IN WHOLE OR IN PART) USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY. ANY COPIES OF THIS DRAWING/DOCUMENT MADE BY ANY METHOD MUST ALSO INCLUDE A COPY OF THIS LEGEND. © 2012

NOTE: UNLESS OTHERWISE STATED THE FOLLOWING APPLIES
1 ISO METHOD A \oplus PROJECTION.
2 S.I. UNITS.
3 SURFACE FINISH TO BS 308/BS 1134.
4 DIMS. APPLY AFTER CHEMICAL OR ELECTRO-PLATED FINISH.
5 WELD SYMBOLS TO BS 499.
6 DATUM DIMENSIONS.
7 METRIC THREADS TO BS 3643/DIN 13.
8 UNIFIED THREADS TO BS 1580.

ASSOC SPECS.	BS EN 60529		
MATERIAL		DRAWN M. HOLDER	DATE 11-06-12
HEAT TREATMENT		CHECKED	DATE 14/05/13
FINISH		APPROVED SPECIALIST JPH	DATE 14/05/13
FORM		APPROVED FOR ISSUE JPH	DATE 14/05/13

TITLE
POWER TO POWER CABLE UABS
SCALE WAS -
NTS SHEET 1 OF 1

HALDEX BRAKE PRODUCTS LTD
MOONS MOAT DRIVE,
REDDITCH, WORCS.
B98 9HA
Haldex
PART No.
364 591 000 2
A3