



| HALDEX ASSY No | HALDEX SUBASSY No | LENGTH | WEIGHT | ISS | DATE |
|----------------|-------------------|--------|---------|-----|----------|
| 814 026 001 | 003 9493 09 | 1.5 m | 470 g | 1 | 05.03.10 |
| 814 026 011 | 003 9494 09 | 4.5 m | 1.3 kg | 1 | 05.03.10 |
| 814 026 021 | 003 9495 09 | 12 m | 3.25 kg | 1 | 05.03.10 |

Autocad
DRAWING

THIS DRAWING/DOCUMENT IS COPYRIGHT AND THE PROPERTY OF HALDEX BRAKE PRODUCTS LIMITED. IT MUST NOT BE COPIED (IN WHOLE OR IN PART) USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY. ANY COPIES OF THIS DRAWING/DOCUMENT MADE BY ANY METHOD MUST ALSO INCLUDE A COPY OF THIS LEGEND.

NOTE: UNLESS OTHERWISE STATED THE FOLLOWING APPLIES
 1. ISD METHOD A
 2. S.I. UNITS.
 3. SURFACE FINISH TO BS 308/BS 1134.
 4. DIMS. APPLY AFTER CHEMICAL OR ELECTRO-PLATED FINISH.
 5. WELD SYMBOLS TO BS 499.
 6. D. DATUM DIMENSIONS.
 7. METRIC THREADS TO BS 3643/DIN 13.
 8. UNIFIED THREADS TO BS 1580.

ASSOCIATED SPECIFICATIONS

| | |
|--------|--|
| GS0082 | |
| GS0197 | |

| MATERIAL | HEAT TREATMENT | FINISH | FORM |
|----------|----------------|--------|------|
| - | - | - | - |

| DRAWN | CHECKED | APPROVED SPECIALIST | APPROVED FOR ISSUE |
|-------|---------|---------------------|--------------------|
| PL | | JPH | JPH |

| DATE | DATE | DATE | DATE |
|----------|----------|----------|----------|
| 05.03.10 | 05.03.10 | 05.03.10 | 05.03.10 |

TITLE
 ISD POWER A TO
 DIN-STYLE 7-PIN
 CABLE-ASSEMBLY

ORIGINAL SCALE
 NTS
 WAS
 SHEET 1 OF 1

HALDEX BRAKE PRODUCTS LTD.
 MDONS WQAT DRIVE, REDDITCH, WORCS. B96 7HA
 PART No. 814 026 000 2

COMPUTER PRODUCED DRAWING
 MUST NOT BE CHANGED MANUALLY

- N 1 7-POLE, DIN-STYLE BAYONET CONNECTOR
 PIN COLOUR CONFIGURATION:
 PIN 1 - B+P
 PIN 2 - B+IGN
 PIN 3 - B-IGN
 PIN 4 - B-
 PIN 5 - LAMP
 PIN 6 - CAN H
 PIN 7 - CAN L
- N 2 POWER A CONNECTOR - BLUE
 SOCKET 1 - B+P
 SOCKET 2 - B-IGN
 SOCKET 3 - CAN L
 SOCKET 4 - B+IGN
 SOCKET 5 - LAMP
 SOCKET 6 - B-
 SOCKET 7 - CAN H
- N 3 PROTECTIVE CAP - DO NOT REMOVE UNTIL FITMENT TO ECU.
- N 4 'D'-RING TO BE PROTECTED FROM DAMAGE PRIOR TO ASSEMBLY.
- N 5 CABLE OUTER SHEATH MATERIAL: PVC
- N 6 PART NUMBER IDENTIFICATION.

THIS DRAWING/SPECIFICATION USES CLASSIFIED CHARACTERISTIC SYMBOLS DEFINED IN QUALITY PROCEDURE 4.17