



PART No. 364 616 000 2

COMPUTER PRODUCED DRAWING
MUST NOT BE CHANGED MANUALLY

- N 1 APPROXIMATE MASS OF ASSEMBLY: 33g
- N 2 CONFORMS TO IP54 RATING (BS EN 60529) WHEN CONNECTED TO LOOM.
- N 3 VOLTAGE: 24V
- N 4 BEEPER IS TO BE SECURED TO A FLAT AREA, MOUNTED IN ORIENTATION AS SHOWN.
- N 5 BEEPER IS TO BE SECURED WITH AN M3.5 STAINLESS STEEL SCREW. TIGHTEN TO A MAXIMUM TORQUE OF 1.3Nm. FASTENER TO BE PROTECTED FROM CORROSION TO GIVE 200 HOURS SALT SPRAY RESISTANCE.
- N 6 THIS PRODUCT IS FULLY COMPLIANT WITH ADR.
- N 7 SOUND LEVEL: 108 ± 5 dB AT 0.3m CONTINUOUS SOUND.
- N 8 FOR INSTALLATION INSTRUCTIONS REFER TO THE LATEST VERSION OF DOCUMENT 006 300 035 ON FINDEX.
- N 9 SOUND DIFFUSION HOLES.
- N10 LABEL (NOT SHOWN). LABEL DETAILS: INTERNAL PART No., TRACABILITY CODE, BARCODE AND DATE OF MANUFACTURE.

PART NUMBER:
364 616 001

K **M**
T THIS DRAWING/SPECIFICATION USES CLASSIFIED CHARACTERISTIC SYMBOLS DEFINED IN QUALITY PROCEDURE 4.17

1	PR2151_4	MPH	24-07-14				
ISS	CHANGE	CHEC	DATE	ISS	CHANGE	CHEC	DATE

THIS DRAWING/DOCUMENT IS COPYRIGHT AND THE PROPERTY OF HALDEX BRAKE PRODUCTS LIMITED. IT MUST NOT BE COPIED (IN WHOLE OR IN PART) USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY. ANY COPIES OF THIS DRAWING/DOCUMENT MADE BY ANY METHOD MUST ALSO INCLUDE A COPY OF THIS LEGEND. © 2014

NOTE: UNLESS OTHERWISE STATED THE FOLLOWING APPLIES
 1 ISO METHOD A PROJECTION.
 2 S.I. UNITS.
 3 SURFACE FINISH TO BS 308/BS 1134.
 4 DIMS. APPLY AFTER CHEMICAL OR ELECTRO-PLATED FINISH.
 5 WELD SYMBOLS TO BS 499.
 6 D DATUM DIMENSIONS.
 7 METRIC THREADS TO BS 3643/DIN 13.
 8 UNIFIED THREADS TO BS 1580.

ASSOC SPECS.	BS EN 60529		
MATERIAL		DRAWN M. HOLDER	DATE 24-07-14
HEAT TREATMENT		CHECKED <i>Kalpe</i>	DATE 25/07/14
FINISH		APPROVED SPECIALIST <i>OTF</i>	DATE 25/07/14
FORM		APPROVED FOR ISSUE	DATE 28/07/14

TITLE
BEEPER
EB+ SOFT DOCKING

ORIGINAL SCALE 3:4
WAS —
SHEET 1 OF 1

HALDEX BRAKE PRODUCTS LTD
MIRA TECHNOLOGY PARK,
LINDLEY,
WARWICKSHIRE,
CV13 6DE

Haldex

PART No. 364 616 000 2