

Easy to install and eliminates hose binding



Hose lengths and sizes to fit your application.

- Live design allows for movement without binding during and post installation
- Quick & easy single wrench installs
- Double O-ring leak free design
- Live swivel design featuring all brass construction to eliminate corrosion
- Rugged hose construction for maximum life: resistant to UV, ozone, fuels and commonly used road chemicals
- Operating temperature of -40°F to +200°F (-40°C to +93°C), operating pressure to 225 PSI
- Meets or exceeds SAE J1402 - Type A - DOT FMVSS - No. 106 Brake Hoses, 49 CFR 571.106

Sold through cooperation with Tectran® All trademarks and patents (9869416) are property of their respective owners. See literature #L56001 on haldex.com for more information.

3/8" Hose 3/8" Fittings – Both Ends

Part Number	Length
M5LS6616	16"
M5LS6618	18"
M5LS6620	20"
M5LS6622	22"
M5LS6624	24"
M5LS6626	26"
M5LS6628	28"
M5LS6630	30"
M5LS6632	32"
M5LS6634	34"
M5LS6636	36"
M5LS6638	38"
M5LS6640	40"
M5LS6642	42"
M5LS6644	44"
M5LS6646	46"
M5LS6648	48"
M5LS6650	50"
M5LS6652	52"
M5LS6654	54"
M5LS6656	56"
M5LS6658	58"
M5LS6660	60"
M5LS6672	72"
M5LS6684	84"

1/2" Hose 3/8" Fittings – Both Ends

Part Number	Length
M5LS8616	16"
M5LS8618	18"
M5LS8620	20"
M5LS8622	22"
M5LS8624	24"
M5LS8626	26"
M5LS8628	28"
M5LS8630	30"
M5LS8632	32"
M5LS8634	34"
M5LS8636	36"
M5LS8638	38"
M5LS8640	40"
M5LS8642	42"
M5LS8644	44"
M5LS8646	46"
M5LS8648	48"
M5LS8650	50"
M5LS8652	52"
M5LS8654	54"
M5LS8656	56"
M5LS8658	58"
M5LS8660	60"
M5LS8672	72"
M5LS8684	84"

45° Female Dual Swivel Hose Fittings



Meets the toughest standard in the industry – yours



Hose assembly solutions that meet your requirements.

- Direct replacement hoses for late model Peterbilt and Kenworth
- Female 45° flare swivel, all brass fittings on both ends
- Rugged hose construction for maximum life: resistant to UV, ozone, fuels and commonly used road chemicals
- Operating temperature of -40°F to +200°F (-40°C to +93°C), operating Pressure to 225 psi
- Meets or exceeds SAE J1402 - Type A - DOT FMVSS - No. 106 Brake Hoses, 49 CFR 571.106

3/8" Hose 3/8" Fittings – Both Ends

Part Number	Length
M5FF6616	16"
M5FF6618	18"
M5FF6620	20"
M5FF6622	22"
M5FF6624	24"
M5FF6626	26"
M5FF6628	28"
M5FF6630	30"
M5FF6632	32"
M5FF6634	34"
M5FF6636	36"
M5FF6638	38"
M5FF6640	40"
M5FF6642	42"
M5FF6644	44"
M5FF6646	46"
M5FF6648	48"
M5FF6650	50"
M5FF6652	52"
M5FF6654	54"
M5FF6656	56"
M5FF6658	58"
M5FF6660	60"
M5FF6672	72"
M5FF6684	84"

1/2" Hose 3/8" Fittings – Both Ends

Part Number	Length
M5FF8616	16"
M5FF8618	18"
M5FF8620	20"
M5FF8622	22"
M5FF8624	24"
M5FF8626	26"
M5FF8628	28"
M5FF8630	30"
M5FF8632	32"
M5FF8634	34"
M5FF8636	36"
M5FF8638	38"
M5FF8640	40"
M5FF8642	42"
M5FF8644	44"
M5FF8646	46"
M5FF8648	48"
M5FF8650	50"
M5FF8652	52"
M5FF8654	54"
M5FF8656	56"
M5FF8658	58"
M5FF8660	60"
M5FF8672	72"
M5FF8684	84"

Use of brands Peterbilt and Kenworth is for the purpose of common application only.

To learn more about the Midland line of products from Haldex, please visit haldex.com

United States 816-891-2470
Canada 519-621-6722
Mexico 52-81-81569500

L19012
4/19 US 5M ALP
Printed in the USA